

# SPECIAL FLUIDS HOT WATER AND STEAM

## Product Index



| Function  | $\Delta P$ |            | Temperature |           | Pipe connections   | Series          | Page                   |
|---|------------|------------|-------------|-----------|--|-----------------|------------------------|
|   | min. (bar) | max. (bar) | min. (°C)   | max. (°C) |  |                 |                        |
| <b>SOLENOID VALVES, BRASS BODY</b>                    |            |            |             |           |  |                 |                        |
| 2/2 NC  | 0          | 6          | -20         | +165      | 1/4 - 3/8  | 263             | V901-09                |
| 2/2 NC  | 0          | 9          | -20         | +150      | 3/8 .. 3/4   | 222             | V901-15                |
| 2/2 NC  | 0,4        | 8          | +60         | +170      | 3/8 .. 1   | 240             | V901-21                |
| 2/2 NC  | 0,35       | 10         | -20         | +184      | 3/8 .. 2   | 220             | V901-25                |
| <b>PRESSURE OPERATED VALVES, BRONZE BODY</b>          |            |            |             |           |  |                 |                        |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      | 3/8 .. 2 1/2   | E290            | V901-46-1              |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      | Flanged  | DN 25 .. 50     | T290 V901-46-1         |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      |  | 1/2 .. 2        | 165 (AD/TBT) V901-46-3 |
| 2/2 NC  | 0          | 16         | -10         | +184      | Flanged  | DN 15 .. 80     | 165 (AD/BBT) V901-46-3 |
| 3/2 NC-NO   | 0          | 16         | -10         | +184      |  | 1/2 .. 2        | E390 V901-46-1         |
| 3/2 NO  | 0          | 16         | -10         | +184      |  | 1/2 .. 2        | 166 (AD/TBT) V901-46-3 |
| <b>PRESSURE OPERATED VALVES, STAINLESS STEEL BODY</b> |            |            |             |           |  |                 |                        |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      |  | 3/8 .. 2 1/2    | E290 V901-46-1         |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      | External thread  | 1/2 .. 1        | U290 V901-46-1         |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      | External thread, food connections DIN 11851              | Rd 28x8 .. 44x6 | Y290 V901-46-1         |
| 2/2 NC-NO   | 0          | 16         | -10         | +184      | Clamp / butt welding                                     | DN 10 .. 65     | S290 V901-46-1         |
| 2/2 NC  | 0          | 16         | -10         | +184      | Operator with ISO 15218 (CNOMO, size 15) pilot interface | 3/8 .. 3/4      | E290 V901-46-1         |
| 2/2 NC-NO   | 0          | 40         | -25         | +250      |  | 1/2 .. 2        | E298 V901-46-2         |
| 2/2 NC-NO   | 0          | 40         | -25         | +250      | Flanged (DIN and ANSI Class 300)                         | DN 15..50       | T298 V901-46-2         |
| 2/2 NC-NO   | 0          | 40         | -25         | +250      | Socket welding ends                                      | DN 15..50       | S298 V901-46-2         |
| 3/2 U   | 0          | 40         | -25         | +250      |  | 1/2 .. 2        | E398 V901-46-2         |
| 3/2 U   | 0          | 40         | -25         | +250      | Flanged (DIN and ANSI Class 300)                         | DN 15..50       | T398 V901-46-2         |
| 3/2 U   | 0          | 40         | -25         | +250      | Socket welding ends                                      | DN 15..50       | S398 V901-46-2         |
| 2/2 NC-NO   | 0          | 24         | -10         | +223      | External thread  | M25x1,5..M36x2  | R298 V901-54           |
| 2/2 NC-NO   | 0          | 24         | -10         | +223      | Pad mounting   | DN 10 .. 32     | R298 V901-56           |
| <b>PRESSURE OPERATED VALVES, STEEL BODY</b>           |            |            |             |           |  |                 |                        |
| 2/2 NC  | 0          | 25         | -10         | +184      | Flanged  | DN 15 .. 50     | 165 (AD/BA) V901-46-3  |

