

SPECIAL FLUIDS VACUUM SERVICE

Product Index



| Function | Abs. pressure | | Temperature | | Pipe connections | Series | Page |
|--|-----------------------|----------------------|-------------|---------------------|--|----------------------|-------------|
| | min. (mbar) | min. (Torr) | min. (°C) | max. (°C) | | | |
| SOLENOID VALVES, BRASS BODY | | | | | | | |
| NC | 1,33.10 ⁻⁶ | 10 ⁻⁶ | -20 | +90 | 1/4 | 262 | V904-10 |
| NC | 1,33.10 ⁻⁶ | 10 ⁻⁶ | -20 | +90 | 3/8 - 1/2 | 030 | V904-15 |
| NC-NO | 1,33.10 ⁻⁶ | 10 ⁻⁶ | -20 | +90 | 3/8 .. 3/4 | 210 | V904-20 |
| 2/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 287 | Sect.C/V272 |
| 3/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 387 | Sect.E/V577 |
| SOLENOID VALVES, ALUMINIUM BODY | | | | | | | |
| NC | 1,33.10 ⁻⁶ | 10 ⁻⁶ | -20 | +90 | 1 .. 2 | 215 | V904-25 |
| SOLENOID VALVES, STAINLESS STEEL BODY | | | | | | | |
| 2/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 287 | Sect.C/V272 |
| VALVES, BRASS BODY | | | | | | | |
| 2/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 287 | Sect.D/V485 |
| 3/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 387 | Sect.F/V785 |
| VALVES, BRONZE BODY | | | | | | | |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 ⁽¹⁾ | 3/8 .. 2 1/2 | E290 | Sect.D/V410 |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 | Flanged ⁽¹⁾ DN 25..50 | T290 | Sect.D/V431 |
| 3/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 ⁽¹⁾ | 1/2 .. 2 | E390 | Sect.F/V703 |
| VALVES, STAINLESS STEEL BODY | | | | | | | |
| 2/2 NC-NO | 10 ⁻⁴ | 7,5.10 ⁻⁵ | -20 | +100 | Coaxial 3/8 .. 1 | 287 | Sect.D/V485 |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 ⁽¹⁾ | 1/2..2 1/2 | E290 | Sect.D/V410 |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 | External thread ⁽¹⁾ 1/2..1 | U290 | Sect.D/V412 |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 | Ext. thread, foods connections DIN 11851 ⁽¹⁾ RD 28x1/8 .. 44x1/6 | Y290 | Sect.D/V414 |
| 2/2 NC-NO | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 | Clamp / Butt welding ⁽¹⁾ DN 10..65 | S290 | Sect.D/V420 |
| 2/2 NC | 1,33.10 ⁻³ | 10 ⁻³ | -10 | +184 | Int. or ext. thread, DIN 11851, clamp, butt welding ⁽¹⁾ Operator with ISO 15218 (CNOMO, size 15) pilot interface | DN 10..65 E/U/Y/S290 | Sect.D/V438 |
| 2/2 NF-NO | 10 ⁻² | 10 ⁻² | -25 | +250 | 1/2 .. 2 | E298 | Sect.D/V451 |
| 2/2 NF-NO | 10 ⁻² | 10 ⁻² | -25 | +250 | Flanged (DIN and ANSI Class 300) DN 15..50 | T298 | Sect.D/V453 |
| 2/2 NF-NO | 10 ⁻² | 10 ⁻² | -25 | +250 | Socket welding ends DN 15..50 | S298 | Sect.D/V455 |
| 3/2 U | 10 ⁻² | 10 ⁻² | -25 | +250 | 1/2 .. 2 | E398 | Sect.F/V751 |
| 3/2 U | 10 ⁻² | 10 ⁻² | -25 | +250 | Flanged (DIN and ANSI Class 300) DN 15..50 | T398 | Sect.F/V753 |
| 3/2 U | 10 ⁻² | 10 ⁻² | -25 | +250 | Socket welding ends DN 15..50 | S398 | Sect.F/V755 |

⁽¹⁾ With FPM disc, see page V435.

(Potentially explosive atmospheres, see page 2)

All leaflets are available on: www.asconumatics.eu

